## REPAIRABILITY INDEX CALCULATION AND PRESENTATION OF THE PARAMETERS WHICH ALLOWED TO ESTABLISH IT

Washing machine

Date of calculation	19/03/2021	
Producer's or importer's name or trademark	Candy Hoover groupe	
Producer or importer adress	53 bd Ornano 93200 Saint Denis	
Producer's or importer's model identifier	31011358/CSSD1413TWMCBE47	

This "FINAL\_SCORE" tab in English is purely indicative. In order to meet regulatory obligations, only the "NOTE\_FINALE" tab in French (see the next tab) is to be sent. Note: The results are automatically reported in the French tab.

	(see the next tab) is to be sent. Note. The results are automatically repor	tea iii tiie i ie	men tabi		
Criteria	Sub-criteria	Score of subcriterion /10	Weighting factor of subcriterion	Score of criterion /20	Total criteria scores /100
CRITERION 1 : DOCUMENTATION	1.1 Availability of the technical documentation and other documentation related to user and maintenance instructions	6,5	2	13,1	
DISASSEMBLY, ACCESSIBILITY, TOOLS,	2.1 Ease of disassembly parts from List 2*	6,7	1		
	2.2 Necessary tools (List 2)	9,0	0,5	15,5	
	2.3 Fasteners characteristics parts from List 1** and List 2	8,6	0,5		
CRITERION 3 : AVAILABILITY OF SPARE PARTS	3.1 Availability over time parts from List 2	5,4	1		
	3.2 Availability over time parts from List 1	5,4			75,4
	3.3 Delivery time parts from List 2	5,8	0,3	11,4	75,4
	3.4 Delivery time parts from List 1	7,5	0,2		
CRITERION 4 : PRICE OF SPARE PARTS	4. Ratio between price of parts from list 2 to the price of the product	9,0	2	18,0	
CRITERION 5 : SPECIFIC CRITERION	5.1 Accessibility of usage-counter to consumers	10,0	1		
	5.2 Free remote assistance	10,0	0,5	17,5	
	5.3 Possibility to reset softwares	5,0	0,5		
Reparability index on 10					7,5

<sup>\*</sup> list 2: list of a maximum of 3 to 5 spare parts (depending on the category of equipment concerned) whose broken or malfunctioning parts are the most frequent;
\*\* list 1: list of a maximum of 10 other spare parts (depending on the category of equipment concerned) whose good condition is necessary for the operation of the equipment.